

# TremPly® TPO Bonding Adhesive LV3

An Accessory Designed for TremPly TPO Single Ply Roof System



## FEATURES

- Low VOC (<250 g/l)
- Roller or brush applied
- Approximately 3 square coverage in a 5 gallon can.

## BENEFITS

- Low odor application, environmentally friendly
- Ease of application
- Extended square ft. coverage

## DESCRIPTION

TremPly® TPO Bonding Adhesive LV3 is a contact-type bonding adhesive specially designed for bonding non-fleece back TPO single-ply roofing membranes (non-fleece back) and flashings to various roofing substrates.

## BASIC USES

TremPly® TPO Bonding Adhesive LV3 contains less than 250 grams per liter of Volatile Organic Compounds (VOCs) and has been formulated using a blend of VOC-exempt and non-exempt solvents to be in compliance with air-quality regulations for single-ply roofing adhesives.

## COLOR

Amber

## PACKAGING

5-gallon pails (18.925-liter 38 pails) Weight, 38 lbs (17.24 kg.) per pail; 45 pails per pallet

## COVERAGE

50-60 sq. ft./gallon applied half to substrate and half to the sheet back (1.23 - 1.47 m<sup>2</sup>/liter)

## SHELF LIFE

1 year, unopened

## STORAGE

Recommended storage temperature is between 60°F - 80°F. Storage for continued periods outside this temperature range may shorten shelf life. Installation Temperature: 40°F (4°C) and rising.

## PHYSICAL PROPERTIES

**Base:** Synthetic polymer

**Solvent:** VOC-compliant blend

**Flash point:** 30.2°F (-1°C)

**Viscosity:** Nominal 2,750 cps

**Total Solids:** 25% +/- 1%

**Voc:** <250 g/l

**Open Time:** Up to 60 minutes

**Dry Time:** 15- 25 minutes, depending on weather conditions

**Application:** Roller, brush, or spray

## MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

## PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.

## TECHNICAL SUPPORT



Roofing & Building Maintenance

[www.tremcoroofing.com](http://www.tremcoroofing.com)  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013

220 Wicksteed Avenue  
Toronto, Ontario, M4H 1G7  
1.800.668.9879

Tremco Roofing and Building Maintenance is part of Tremco Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.